

## AFTER CARE INSTRUCTIONS FOR WOCA OIL FINISHED KASWELL END GRAIN FLOORING

# DO NOT CLEAN BY WET MOPPING

### Recommended Cleaning Products: Woca Soap Spray, Woca Refresh Spray, and Woca Commercial Oil Cleaner

To protect your investment and to ensure that your Kaswell oil finished flooring maintains its beauty, with years of lasting service, we offer the following recommendations for care and maintenance.

#### **CAUTION: DIRECT WETTING WILL DAMAGE THE OIL FINISH AND THE WOOD FLOORING**

The best way to care for your oil finished flooring must include daily sweeping. Clean spills as they occur with a clean dry cloth, and use Woca Natural Soap Spray to spot clean the area. Use of other manufacturer's cleaning products are not advised.

The beauty of an oil finished floor is that it can be revitalized or refinished without the necessity for re-sanding. If your flooring has NOT been regularly cared for with Woca Soap Spray or Woca Refresh Spray, it will definitely benefit from a machine buff cleaning with the Woca Commercial Cleaning Oil. The Woca cleaning oil will keep the floor properly saturated with oil, helping to keep dirt at the surface rather than allowing it to settle in the wood. With proper ventilation and application, Woca Commercial Oil Cleaner work can be done in the evening and walked on the following morning.

#### **FOR DAILY AND WEEKLY CARE**

Daily sweeping is always recommended to remove sand or other abrasive particles that will harm the finish. Use a micro-fiber mist mop, or spray Woca Natural Soap Spray directly from the bottle to remove dirt and debris. Wipe dry immediately.

#### **FOR MONTHLY OR QUARTERLY CARE**

Use Woca Refresh Spray in high traffic areas, by mist mop application, or from the spray bottle itself. Wipe dry immediately.

**CAUTION:** Woca Soap Spray and Woca Refresh Spray contain water, and therefore **MUST** be used by spray application only. Both products are available in white or natural.

#### **FOR BI-ANNUAL, ANNUAL, OR ANYTIME CARE & CLEANING**

In place of soap spray and refresh spray, use Woca Commercial Oil Cleaner. The cleaning oil contains no water, and therefore cannot harm the wood. The cleaning oil requires use of a slow speed buffer, buffing pads, and cotton cloths or towels.

Two methods of application:

1. Spray the Commercial Oil Cleaner on a small area, then buff with soft absorbent cloths. Do not let sprayed areas rest for more than one hour. Be sure to buff off all excess oil. You can not over buff. So, if you are not sure you've buffed enough, buff again...Or
2. Soak a soft cloth in the Commercial Oil Cleaner, then wring it out. Place the cloth below a 3M white pad, and place the 3M pad and cloth below a standard 1100 RPM buffer. Buff clean with the cloth, then dry buff with a new cloth. Repeat the process if needed. Contact a Kaswell Representative for our video displaying this maintenance process. Again, if you are not sure you've buffed enough, buff again. Any excess oil left on the surface will attract dust and dirt. This can lead to surface marks such as footprints. Approximate drying time: 8-12 hours.

High traffic commercial spaces would benefit from more frequent planned maintenance with the Commercial Oil Cleaner. For standard residential care or for light commercial office space, schedule Commercial Oil Cleaner application once every 12 months or when needed.

**WARNING: Rags, pads, or other waste products soaked with Woca Commercial Oil Cleaner may self ignite if improperly discarded. Remember, there is no water in this product, so immediately after use place all rags and waste in a sealed water-filled bags for proper disposal.**